

Platea D11 -Developer



*Developer for Thermal and CTcP-UV positive plates.
Ready to use.*

Properties.

- ✓ *DURABILITY: Its specific formulation permits high productivity in square meters developed.*
- ✓ *CLEANING: Its dissolution capability reduces the accumulation of emulsion in the filters, rollers and bath tank, keeping them cleaner.*
- ✓ *COMPATIBILITY: Capable to develop the major positive Thermal CTP (except closed systems) and CTcP UV plates.*
- ✓ *Non-aggressive to the anodizing layer of the plates.*
- ✓ *With buffered agents to minimize the aggression to the image area.*
- ✓ *It contains corrosion inhibitors.*
- ✓ *Conductivity: 81 mS.*

How to use.

Processor parameters:

▪ Working temperature.....			23 ± 1°C
▪ Dwell time			30 ± 5 seconds
▪ Replenisher			120 cc / m ²
	Antiox.	ON.....	100 cc / h
	Antiox.	OFF.....	100 cc / h

Packaging

- ✓ 20 litros.
- ✓ 200 litros.
- ✓ 1.000 litros.

PLATEA
g r a p h i c

Juan Fernandez i Comas, 3
08940 Cornellá (Barcelona) España
Tel: +34 93 4457553
E-mail: info@plateatc.com www.plateatc.com